

# Backuppc Hostcheck für Ubuntu und Gentoo

Du möchtest dich gerne für unsere Hilfe erkenntlich zeigen 🙏 . Gerne. Wir bedanken uns bei dir für deine Spende! ☐

**Spenden**

Zum frei verfügbaren [Apt-Repository](#)



GITLAB:

Das offizielle Checkscript von Backuppc das überprüft ob alle Rechner gebackuped sind ist veraltet und nicht brauchbar. Das Script wurde für Gentoo und Ubuntu umgeschrieben. Folgender Eintrag muss jeweils in die **/etc/suduers**:

```
nagios    ALL=(backuppc) NOPASSWD: ALL
```

Die Scripte werden jeweils in das Nagios Pluginverzeichnis kopiert.

## Checksript für Gentoo

[check\\_hosts\\_status](#)

```
#!/usr/bin/perl -w
#
# Nagios module to check backups from BackupPC software v0.2
# Made by Pierre Mavro
# Last Modified : 04/04/2009
#
# This Nagios module is under GPLv2 License
#
#####
#
# Installation (nagios client side) :
# - Copy the script in your nagios plugins directory (usually
/usr/lib/nagios/plugins)
# - Set good rights (700 for nagios user)
# - Add those two lines in your suders file :
#   - "Cmd_Alias GETSTATUS = /bin/su - backuppc -c
/usr/share/backuppc/bin/BackupPC_serverMesg (or replace by your
$bppccmd value bellow) 'status hosts'"
#   - "nagios ALL=NOPASSWD:GETSTATUS"
#
```

```
# Usage : check_backuppc_hosts [path_to_BackupPC_serverMesg]
#         - path_to_BackupPC_serverMesg : if unset, default is
/usr/share/backuppc/bin/BackupPC_serverMesg
#
#####
#
#
# History :
#
# v0.2 :
# + Added number of backed hosts in status information column
# + Added number of hosts errors in status information column
# + Added an unknow host detection (from host backuppc file)
# = Check hosts method optimized ((x hosts) * (time to check) faster)
# = Improved security on sudoers command
#
# v0.1 :
# + First version
#
#####
#

use strict;

my @hosts_list;
my @errors;
my @formatted_bppccmd;
my $bppccmd='/usr/bin/BackupPC_serverMesg';

# Get list of all backed hosts
sub format_input {
    # Test $bppccmd execution
    die "Could not execute $bppccmd file : $!" unless (-x $bppccmd);
    # Only bakcuppc user could check backup state
    open (COMMANDBACKUPPC, "/usr/bin/sudo -u backuppc $bppccmd
'status hosts' |") or die "Couldn't execute $bppccmd 'status hosts' :
$!";
    # open (COMMANDBACKUPPC, "/usr/bin/sudo /bin/su - backuppc -c
\"$bppccmd 'status hosts'\" |") or die "Couldn't execute $bppccmd
'status hosts' : $!";
    while (<COMMANDBACKUPPC>) {
        @formatted_bppccmd = split /,/, $_;
    }
    close (COMMANDBACKUPPC);
}

# Check backup status for each hosts
sub check_hosts_status {
    &format_input;
    foreach (@formatted_bppccmd) {
```

```

    chomp $_;
    my $current_host;
    # Add host to hosts_list
    if (/\"(\S+)\" => {/) {
        push @hosts_list, $1;
        $current_host=$1;

        # Verify if any errors has occurred during backup
        if (/\"error\" => \"(.+?)\"/i) {
            push @errors, \"$current_host : $1\";
        }
    }
}

# Give result to Nagios
sub feedback {
    my $total_errors = @errors;
    if ($total_errors ne 0) {
        my $many='';
        $many='s' if ($total_errors > '1');
        my @formatted_errors = join \" - \", @errors;
        print \"[$total_errors problem\".\"$many\".\"] -
@formatted_errors\\n\";
        exit(2);
    } else {
        my $total_hosts = @hosts_list;
        print \"All ($total_hosts) servers have been correctly
backedup\\n\";
        exit(0);
    }
}

# Check if first arg has been set
$bppccmd=$ARGV[0] if (defined($ARGV[0]));

# Check if 1 or less args has been set
if (@ARGV <= 1) {
    &check_hosts_status;
    &feedback;
} else {
    print \"Usage : check_backuppc_hosts
[path_to_BackupPC_serverMesg]\\n- path_to_BackupPC_serverMesg : if
unset, default is /usr/share/backuppc/bin/BackupPC_serverMesg\\n\\n\";
    exit(-1);
}

```

# Checkscript Ubuntu (Getestet auf 12.04 LTS 64bit)

## check\_hosts\_status

```
#!/usr/bin/perl -w
#
# Nagios module to check backups from BackupPC software v0.2
# Made by Pierre Mavro
# Last Modified : 04/04/2009
#
# This Nagios module is under GPLv2 License
#
#####
#
# Installation (nagios client side) :
# - Copy the script in your nagios plugins directory (usually
/usr/lib/nagios/plugins)
# - Set good rights (700 for nagios user)
# - Add those two lines in your suoders file :
#   - "Cmd_Alias GETSTATUS = /bin/su - backuppc -c
/usr/share/backuppc/bin/BackupPC_serverMesg (or replace by your
$bppccmd value bellow) 'status hosts'"
#   - "nagios ALL=NOPASSWD:GETSTATUS"
#
# Usage : check_backuppc_hosts [path_to_BackupPC_serverMesg]
#         - path_to_BackupPC_serverMesg : if unset, default is
/usr/share/backuppc/bin/BackupPC_serverMesg
#
#####
#
# History :
#
# v0.2 :
# + Added number of backed hosts in status information column
# + Added number of hosts errors in status information column
# + Added an unknow host detection (from host backuppc file)
# = Check hosts method optimized ((x hosts) * (time to check) faster)
# = Improved security on sudoers command
#
# v0.1 :
# + First version
#
#####
#

use strict;
```

```

my @hosts_list;
my @errors;
my @formatted_bppccmd;
my $bppccmd='/usr/share/backuppc/bin/BackupPC_serverMesg';

# Get list of all backed hosts
sub format_input {
    # Test $bppccmd execution
    die "Could not execute $bppccmd file : $!" unless (-x $bppccmd);
    # Only backuppc user could check backup state
    open (COMMANDBACKUPPC, "/usr/bin/sudo -u backuppc $bppccmd
'status hosts' |") or die "Couldn't execute $bppccmd 'status hosts' :
$!";
    # open (COMMANDBACKUPPC, "/usr/bin/sudo /bin/su - backuppc -c
|$bppccmd 'status hosts'|" |") or die "Couldn't execute $bppccmd
'status hosts' : $!";
    while (<COMMANDBACKUPPC>) {
        @formatted_bppccmd = split /},/, $_;
    }
    close (COMMANDBACKUPPC);
}

# Check backup status for each hosts
sub check_hosts_status {
    &format_input;
    foreach (@formatted_bppccmd) {
        chomp $_;
        my $current_host;
        # Add host to hosts_list
        if (/("\S+") => {/} {
            push @hosts_list, $1;
            $current_host=$1;

            # Verify if any errors has occurred during backup
            if (/("error" => "(.+?)"/i) {
                push @errors, "$current_host : $1";
            }
        }
    }
}

# Give result to Nagios
sub feedback {
    my $total_errors = @errors;
    if ($total_errors ne 0) {
        my $many='';
        $many='s' if ($total_errors > '1');
        my @formatted_errors = join " - ", @errors;
        print "[ $total_errors problem.".$many." ] -
@formatted_errors\n";
        exit(2);
    }
}

```

```
    } else {
        my $total_hosts = @hosts_list;
        print "All ($total_hosts) servers have been correctly
backuped\n";
        exit(0);
    }
}

# Check if first arg has been set
$bppccmd=$ARGV[0] if (defined($ARGV[0]));

# Check if 1 or less args has been set
if (@ARGV <= 1) {
    &check_hosts_status;
    &feedback;
} else {
    print "Usage : check_backuppc_hosts
[path_to_BackupPC_serverMsg]\n- path_to_BackupPC_serverMsg : if
unset, default is /usr/share/backuppc/bin/BackupPC_serverMsg\n\n";
    exit(-1);
}
```

From:  
<https://www.deepdoc.at/dokuwiki/> - DEEPDOC.AT - enjoy your brain

Permanent link:  
[https://www.deepdoc.at/dokuwiki/doku.php?id=server\\_und\\_serverdienste:backuppc\\_hostcheck\\_fur\\_ubuntu\\_und\\_gentoo](https://www.deepdoc.at/dokuwiki/doku.php?id=server_und_serverdienste:backuppc_hostcheck_fur_ubuntu_und_gentoo)

Last update: 2025/11/29 22:06

